

Method 508mod-

Date Extracted 2/15/02

Page 90

Lab #	Description	Sample vol/wt	Drip rate ml/min	Surr add	Spk add	IS add	Final vol.	T.V. pos.	pH	Count
1B		500ml		1ml			1ml	3B	7	
REF								4B		
REF								9B		
1946	reext							9A		
1941	reext							1B		
1943	reext							1A		
3438								4A		
3439								7A		
3440								10A		
3441								8B		
3454								7B		
3471								8A		
3472								10B		
Remarks										
Reviewed by, <u>[Signature]</u>										
drip rate must be between 5-15 ml/min for liq-liq extractors drip rate - Extraction type - <u>sep fun</u> Solv. lot# <u>V39466</u> NaCl lot# <u>V39618</u> Na2SO4 lot# <u>V46623</u>										
STANDARD	INT STD LOG#									
CALIBRATION										
REF SPIKE	<u>91759</u>									
MDL/MDRF										
Q. CHECK										
INT. STD.	<u>B110320 2/15</u>									
SURROGATE	<u>GCMs 21606</u>									
LPC										
ENDRIN/DDT										

Analyst [Signature]
revision 4/12/01

Verified by _____

Reviewed by [Signature]
Date 3/14/02

NY e DEP

Price

71.25	939
71.25	917
71.25	1940
71.25	1941
71.25	1942

Smogator
 116, 155
 85
 F, P
 F, P
 F, P

Ref 1
 failed
 failed
 P
 P
 P

Ref 2
 failed
 failed
 F
 F
 P

gmailed