

Method 508

Date Extracted 11/2/07

Page 1

GC/MS

150 parts per million
copy
Sharon

Lab #	Description	Sample vol/wt	Drip rate ml/min	Surr add	Spk add	IS add	Final vol.	T.V. pos.	pH	Count		
	<u>LB J</u>	<u>500mL</u>		<u>1mL</u>			<u>2mL</u>					
	<u>Ref TOX</u>											
	<u>Ref chl/Pest</u>											
	<u>PLL 1016</u>											
	<u>26079 ✓</u>											
	<u>26080 ✓</u>											
	<u>26127 ✓</u>											
	<u>26128 ✓</u>											
	<u>26129 ✓</u>											
	<u>26130 ✓</u>											
	<u>26131 ✓</u>											
	<u>26132 ✓</u>											
	<u>26133 ✓</u>											
	<u>26133 ✓</u>											
<u>26079</u>	<u>SPK chl</u>											
<u>26079</u>	<u>SPK chl dup</u>											
<u>26080</u>	<u>SPK TOX</u>											
<u>26080</u>	<u>SPK TOX dup</u>											
<u>26127</u>	<u>SPK Pest</u>											
<u>26127</u>	<u>SPK Pest dup</u>											
Remarks												
Reviewed by, <u>CB 2/14/02</u>												
drip rate must be between 5-15 ml/min for liq-liq extractors												
Extraction type - <u>Sep Phase</u> Solv. lot# <u>V42E17</u> NaCl lot# <u>V11599</u> Na2SO4 lot# <u>V32603</u>												
STANDARD	INT STD LOG#											
CALIBRATION												
REF/SPIKE												
MDL/MDRF												
Q. CHECK												
INT. STD.												
SURROGATE												
LPC												
ENDRIN/DDT												

Analyst ML/CM/AD
revision 4/12/01

Verified by _____

Reviewed by DW
Date 12/7/11

GC/MS SCANS

QC already submitted
with sample 26079