

Method

508 MOD.

Date Extracted

4/11/02

Page

56

#6CMS 18025

Lab #	Description	Sample vol/wt	Drip rate ml/min	Surr add	Spk add	IS add	Final vol.	T.V. pos.	pH	Count		
L.B.		500 ml		1 ml			1 ml	9B	7			
Ref 1					1 ml			9A				
Ref 2					1 ml			10B				
5846	RE-EXT.							4B				
5852	F.B. / RE-EXT.							2B				
6413	F.B. / RE-EXT.							2A				
6424	RE-EXT.							4A				
6425	RE-EXT.							1B				
6427	RE-EXT.							6A				
6429	RE-EXT.							1A				
8681								7A				
8682								7B				
8683								10A				
8652												
Remarks												
Reviewed by, C/B 3/16/02												
drip rate must be between 5-15 ml/min for liq-liq extractors drip rate -												
Extraction type - SFR FWH		Solv. lot# X01E19		NaCl lot# V39614		Na2SO4 lot# V46648						
STANDARD	INT STD LOG#											
CALIBRATION	HPO4100V											
REF SPIKE	2193											
MDL/MDRF												
Q. CHECK												
INT. STD.	1504080V											
SURROGATE												
LPC												
ENDRIN/DDT												

Analyst

A.D.

revision 4/12/01

Verified by

Reviewed by

Date