

Method 508 MOD.

Date Extracted 3-12-02

Page 148

Ref

#GCM5-17799

Lab #	Description	Sample vol/wt	Drip rate ml/min	Surr add	Spk add	IS add	Final vol.	T.V. pos.	pH	Count		
L.B.		500 ml		1 ml			1 ml	2A	7			
Ref 1					1 ml			10A				
Ref 2					1 ml			7B				
5701								4A				
5702								9A				
5703	F.B.							6A				
5743								7A				
5744								10B				
5745								4B				
5746								2B				
5747								9B				
5748								8B				
5749	See 4/3	↓		↓			↓	8B	↓			
Remarks												
Reviewed by <u>C/B 3/13/02</u>												
drip rate must be between 5-15 ml/min for liq-liq extractors												
drip rate -												
Extraction type - <u>SEP. Fun.</u> Solv. lot# <u>V41470</u> NaCl lot# <u>V39618</u> Na2SO4 lot# <u>V46623</u>												
STANDARD	INT STD LOG#											
CALIBRATION	<u>HPC3010</u>											
(REF) SPIKE	<u>2193</u>											
MDL/MDRF												
Q. CHECK												
INT. STD.	<u>032802</u>											
SURROGATE	<u>2160 D</u>											
LPC												
ENDRIN/DDT												

Analyst A.D.
revision 4/12/01

Verified by hy

Reviewed by DP
Date 4/11/02