

02/08/2000 09:26

1-609-799-8964

CLEANTRONICS

PAGE 02

3

Material Safety Data Sheet

May be used to comply with OSHA's
Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.


HMIS Symbol:

Health	3
Flammability	3
Reactivity	0

NFPA Symbol:

HMIS NFPA
Minimal - 0 - Insignificant
Slight - 1 - Slight
Moderate - 2 - Moderate
Serious - 3 - High
Severe - 4 - Extreme

Fire Reactivity
Special



Identity (As Used on Label and List) # 2913
2wo Oil Soluble Spotter

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

SECTION I

Manufacturer's Name
Cleantronics Inc.

Emergency Telephone Number
1-800-265-3924 CHEM TEL, INC.

Address (Number, Street, City, State, and ZIP Code)

Telephone Number for Information
1-609-799-3312 fax 609-799-8964

19 Washington Rd.
Box 384

Date Prepared
1-28-98

Princeton Jct., NJ 08550

Signature of Preparer (Optional)

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits Recommended	%(Opt.)
Isopropanol	67-63-0	400 ppm	400 ppm	STEL 500 ppm	
Isobutane	75-28-5	800 ppm	800 ppm		
Propane	74-98-6	1000 ppm	Asphyxiant		
(2-Methoxy methylethoxy) - propanol	34590-94-8	100 ppm	100 ppm	STEL 150 ppm	

This product is not known to contain any compound listed and in quantities requiring reporting under SARA Title III Section 303.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

SECTION III Physical/Chemical Characteristics

Boiling Point	180° F	Specific Gravity (H ₂ O = 1)	0.873
Concentrate - Initial		Concentrate	
Pressure (psig. @ 70° F)	40 ± 5	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Butyl Acetate = 1)	No Data
Solubility in Water	Complete	pH	Not Applicable

Appearance and Odor -

Clear colorless liquid with a citrus scent in an aerosol can.

SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test (ASTM D-3065)	Flammable Limits	LEL	UEL
> 8", no flashback; Flammable	No Data	No Data	No Data

Extinguishing Media -

Carbon dioxide, dry chemical, halon, polar or alcohol foam or water spray. Water may be ineffective.

Special Fire Fighting Procedures - Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

Unusual Fire and Explosion Hazards -

Aerosol container (pressurized) may burst if heated over 120° F. Extremely flammable contents.

November 11, 1996