



104 East 25th St
New York, New York 10010
www.atc-enviro.com
212.353.8280
Fax 212.353.8306

February 26, 2002

Mr. Bernard P. Orlan
Director, Environmental Health and Safety
New York City Board of Education
28-11 Queens Plaza North
Long Island City, NY 11101

**Re: Air Sampling for Silica
P. S. 89M
ATC Project No. 15-19125-0297**

Dear Mr. Orlan:

ATC Associates, Inc. (ATC) is pleased to provide this letter report of air sampling for silica-containing dust conducted on February 7, 2002 at the referenced school. The New York City Board of Education (BOE) requested this sampling at the recommendation of Environ Corp., the consultant to the parents association.

Scope of Work

ATC collected ten (10) samples respirable dust using pre-weighed 37mm PVC filters connected to size-selective cyclones to remove the larger (non-respirable) particles prior to deposition on the filters. All samples were collected indoors. The samples were sent to PSC Analytical Services, Inc., an American Industrial Hygiene Association accredited laboratory in Reading, PA. One blank filter was also submitted. Silica analysis was performed by x-ray diffraction according to OSHA Method 142. A copy of the analytical report is attached.

Tenzin Namgyal and Wagdi Abdelshahid, Industrial Hygienists of ATC's New York City office, collected the samples.

Results

Silica was found above the limits of detection in one sample. This was Sample #S4-ATC-0207-89M collected in the Gymnasium. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) for silica-containing dust is based on the percent of quartz (SiO₂) found in the dust, the higher the percentage of quartz, the lower the PEL. The formula for calculating the PEL is found in 29 CFR 1910.1000, Table Z-3. The formula is:

$$\frac{10\text{mg/m}^3}{\% \text{SiO}_2 + 2}$$

Mr. Bernard P. Orlan
Air Sampling for Silica
P. S. 89 (Manhattan)

February 26, 2002

Page 2

ATC Project No. 15-19125-0297

The Gymnasium sample contained 0.0108 milligrams of silica per cubic meter of air (mg/m^3). The amount of quartz in this sample was 22%, therefore the PEL for this dust would be:

$$\frac{10\text{mg}/\text{m}^3}{22+2} = 0.417 \text{ mg}/\text{m}^3$$

The silica concentration in this sample was 2.6% of the calculated PEL.

The OSHA PEL is the only regulatory standard for silica exposure, however it is intended for occupational exposure in settings such as foundries, sandblasting, rock drilling, etc. The EPA does not have an ambient-air quality standard for silica.

ATC appreciates the opportunity to provide this indoor air quality consultative service to the BOE. Please call me at (212) 353-8280 extension 212 if you have any questions.

Sincerely,
ATC Associates, Inc.



James R. Cohn, CIH, CSP
Regional Manager
Industrial Hygiene Division

Attachment