



104 East 25th St., 10th Fl
New York, New York 10010
www.atc-enviro.com
212.353.8280
Fax 212.353.8306

August 5, 2002

Mr. Bernard P. Orlan
Director, Environmental Health and Safety
New York City Board of Education
28-11 Queens Plaza North
Long Island City, NY 11101

**Re: Air Sampling for Silica
P. S. 89M
ATC Project No. 15-19125-0297**

Dear Mr. Orlan:

ATC Associates, Inc. (ATC) is pleased to provide this report of air sampling for silica-containing dust conducted on May 2, 9, 16, 23 and 30, 2002 at the referenced school. The New York City Board of Education (BOE) requested this sampling at the recommendation of Environ Corp., the consultant to the parents association.

Scope of Work

On each day, ATC collected ten (10) samples of respirable dust using pre-weighed 37mm PVC filters connected to size-selective cyclones to remove the larger (non-respirable) particles prior to deposition on the filters. All samples were collected indoors. The samples were sent to PSC Analytical Services, Inc., an American Industrial Hygiene Association accredited laboratory in Reading, PA. One blank filter was also submitted per day. Silica analysis was performed by x-ray diffraction according to OSHA Method 142. Copies of the analytical reports are attached.

Tenzin Namgyal and Wagdi Abdelshahid, Industrial Hygienists from ATC's New York City office, conducted the sampling consistent with accepted industrial hygiene practices. The results represent the conditions on the days the samples were collected.

Results

The Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) for silica-containing dust is based on the percent of quartz (SiO_2) found in the dust, the higher the percentage of quartz, the lower the PEL. The formula for calculating the PEL is found in 29 CFR 1910.1000, Table Z-3. The formula is:

$$\frac{10\text{mg/m}^3}{\% \text{SiO}_2 + 2}$$

The silica sample results of May 2, 9, 16, and 23, 2002, were below the limits of detection.

On May 30, 2002, silica was found above the limits of detection in only one location. This was Sample #ATC-0530-89M-S2, collected in 1st Floor Hallway South.

Mr. Bernard P. Orlan
Air Sampling for Silica
P. S. 89 (Manhattan)

August 5, 2002

Page 2

ATC Project No. 15-19125-0297

The sample (S2) contained 0.005 milligrams of silica per cubic meter of air (mg/m^3). The amount of quartz in this samples was 28%, therefore the PEL for this dust would be:

$$\frac{10\text{mg}/\text{m}^3}{28 + 2} = 0.333\text{mg}/\text{m}^3$$

The silica concentration in this sample was 1.5 % of the calculated PEL.

The OSHA PEL is the only regulatory standard for silica exposure, however it is intended for occupational exposure in settings such as foundries, sandblasting, rock drilling, etc. The EPA does not have an ambient-air quality standard for silica.


ATC appreciates the opportunity to provide this indoor air quality consultative service to the BOE. Please call me at (212) 353-8280 extension 298 if you have any questions.

Sincerely,
ATC Associates, Inc.



Wagdi Abdelshahid
Industrial Hygienist

Reviewed by:



James R. Cohn, CIH, CSP
Regional Manager
Industrial Hygiene Division

Attachment